

Fax: 0049-(0)7223-284-245



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 23.08.2019 Version number 8 Revision: 06.11.2015

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: UHU plus multifest (Härter)
- 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- · Application of the substance / the mixture Adhesives
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

UHU GmbH & Co.KG Herrmannstraße 7 D-77815 Bühl (Baden) Tel.:0049-(0)7223-284-0

email: sds@uhu.boltongroup.de

- · Further information obtainable from: UHU QESH
- · 1.4 Emergency telephone number:

Tel.: + 49 (0) 30/19240 (Notruf) Tel.: + 49 (0) 72 23/28 40

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Flam. Liq. 2 H225 Highly flammable liquid and vapour.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

STOT SE 3 H335 May cause respiratory irritation.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms





GHS02 GHS07

- · Signal word Danger
- Hazard-determining components of labelling: methyl methacrylate

(Contd. on page 2)



Page 2/9

Safety data sheet according to 1907/2006/EC, Article 31

Version number 8 Revision: 06.11.2015 Printing date 23.08.2019

Trade name: UHU plus multifest (Härter)

(Contd. of page 1)

· Hazard statements

H225 Highly flammable liquid and vapour.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H335 May cause respiratory irritation.

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children. P261 Avoid breathing vapours. P280 Wear protective gloves.

P302+P352 IF ON SKIN: Wash with plenty of soap and water.

Dispose of contents/container in accordance with local/regional/national/international

regulations.

· 2.3 Other hazards

· Results of PBT and vPvB assessment

· PBT: Not applicable. · vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.2 Mixtures
- · Description: Adhesive

· Dangerous components:

CAS: 80-62-6 methyl methacrylate

· Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · General information: No special measures required.
- · After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

Supply fresh air; consult doctor in case of complaints.

· After skin contact:

If skin irritation continues, consult a doctor.

Immediately wash with water and soap and rinse thoroughly.

- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing:

Rinse out mouth and then drink plenty of water.

Do not induce vomiting; call for medical help immediately.

· 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

(Contd. on page 3)

50-100%



Page 3/9

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 23.08.2019 Version number 8 Revision: 06.11.2015

Trade name: UHU plus multifest (Härter)

(Contd. of page 2)

• 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · 5.2 Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

- · 5.3 Advice for firefighters
- · Protective equipment:

Wear self-contained respiratory protective device.

No special measures required.

Additional information

Cool endangered receptacles with water spray.

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Particular danger of slipping on leaked/spilled product.

Ensure adequate ventilation

- 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Send for recovery or disposal in suitable receptacles.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Ensure good interior ventilation, especially at floor level. (Fumes are heavier than air).

Prevent formation of aerosols.

· Information about fire - and explosion protection:

Fumes can combine with air to form an explosive mixture.

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles:

Store only in the original receptacle.

(Contd. on page 4)



Page 4/9

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 23.08.2019 Version number 8 Revision: 06.11.2015

Trade name: UHU plus multifest (Härter)

(Contd. of page 3)

Provide solvent resistant, sealed floor.

Store in a cool location.

- · Information about storage in one common storage facility: Store away from oxidising agents.
- · Further information about storage conditions:

Store receptacle in a well ventilated area.

Keep container tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

- · Storage class: 3
- · 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- · Additional information about design of technical facilities: No further data; see item 7.
- · 8.1 Control parameters
- · Ingredients with limit values that require monitoring at the workplace:

80-62-6 methyl methacrylate

IOELV (EU) Short-term value: 100 ppm

Long-term value: 50 ppm

AGW (Germany) Long-term value: 210 mg/m³, 50 ppm

2(I); DFG, EU, Y

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Do not eat, drink, smoke or sniff while working.

The usual precautionary measures are to be adhered to when handling chemicals.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes and skin.

Avoid direct contact with the chemical/ the product/ the preparation by organisational measures.

· Respiratory protection:

Use suitable respiratory protective device when high concentrations are present.

· Protection of hands:

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

After each cleaning use treatment creams, for very dry skin greasy ointments.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 5)





Safety data sheet according to 1907/2006/EC, Article 31

Printing date 23.08.2019 Version number 8 Revision: 06.11.2015

Trade name: UHU plus multifest (Härter)

· Eye protection: Goggles recommended during refilling

(Contd. of page 4)

SECTION 9: Physical and chemical properties · 9.1 Information on basic physical and chemical properties · General Information · Appearance: Form: **Pasty** Yellow Colour: · Odour: Pungent · Odour threshold: Not determined. · pH-value at 20 °C: 5.5 · Change in condition -48 °C Melting point/freezing point: Initial boiling point and boiling range: 101 °C 10 °C · Flash point: · Flammability (solid, gas): Not applicable. 430 °C · Ignition temperature: · Decomposition temperature: Not determined. Product is not selfigniting. Auto-ignition temperature: Product is not explosive. However, formation of · Explosive properties: explosive air/vapour mixtures are possible. · Explosion limits: Lower: 2.1 Vol % **Upper:** 12.5 Vol % · Vapour pressure at 20 °C: 47 hPa · Density at 20 °C: 0.94 g/cm³ · Relative density Not determined. · Vapour density Not determined. · Evaporation rate Not determined. · Solubility in / Miscibility with water at 20 °C: 1.6 g/l Not miscible or difficult to mix. · Partition coefficient: n-octanol/water: Not determined. · Viscosity: Dynamic at 20 °C: 0.6 mPas Kinematic: Not determined. · Solvent content: VOC (EC) 0.00 % (Contd. on page 6)



Page 6/9

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 23.08.2019 Version number 8 Revision: 06.11.2015

Trade name: UHU plus multifest (Härter)

(Contd. of page 5)

Solids content: 2.0 %

• 9.2 Other information All relevant physical data were determined for the

mixture. All non determined data are not measurably or not relevant for the characterization of the mixture.

SECTION 10: Stability and reactivity

- 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

· 10.3 Possibility of hazardous reactions

Reacts with strong acids and alkali.

Reacts with strong oxidising agents.

Forms explosive gases/fumes.

- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: Flammable gases/vapours

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.
- · LD/LC50 values relevant for classification:

80-62-6 methyl methacrylate

Oral LD50 7,872 mg/kg (rat)

- Primary irritant effect:
- · Skin corrosion/irritation
- Causes skin irritation.
- · Serious eye damage/irritation Based on available data, the classification criteria are not met.
- · Respiratory or skin sensitisation

May cause an allergic skin reaction.

- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure

May cause respiratory irritation.

- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.

(Contd. on page 7)



Page 7/9

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 23.08.2019 Version number 8 Revision: 06.11.2015

Trade name: UHU plus multifest (Härter)

(Contd. of page 6)

- 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water Do not allow product to reach ground water, water course or sewage system.

- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Disposal must be made according to official regulations.

· European waste catalogue

08 04 09* waste adhesives and sealants containing organic solvents or other hazardous substances

- · Uncleaned packaging:
- · Recommendation:

Packagings that may not be cleansed are to be disposed of in the same manner as the product.

SECTION 14: Transport information

STABILIZED	· 14.1 UN-Number · ADR, IMDG, IATA	UN1247
STABILISIERT, Lösung	· ADR	1247 METHYLMETHACRYLAT, MONOMER, STABILISIERT, Lösung METHYL METHACRYLATE MONOMER,

- · 14.3 Transport hazard class(es)
- · ADR, IMDG, IATA



· Class 3 Flammable liquids.

· Label

(Contd. on page 8)





Safety data sheet according to 1907/2006/EC, Article 31

Printing date 23.08.2019 Version number 8 Revision: 06.11.2015

Trade name: UHU plus multifest (Härter)

	(Contd. of page
· 14.4 Packing group · ADR, IMDG, IATA	II
· 14.5 Environmental hazards: · Marine pollutant:	No
· 14.6 Special precautions for user · Danger code (Kemler): · EMS Number: · Stowage Category · Stowage Code	Warning: Flammable liquids. 339 F-E,S-D B SW2 Clear of living quarters.
· 14.7 Transport in bulk according to Ar of Marpol and the IBC Code	nnex II Not applicable.
Transport/Additional information:	
· ADR · Limited quantities (LQ) · Excepted quantities (EQ)	1L Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 m
Transport category Tunnel restriction code	2 D/E
· IMDG · Limited quantities (LQ) · Excepted quantities (EQ)	1L Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 m
UN "Model Regulation":	UN 1247 METHYL METHACRYLATE MONOMER STABILIZED, 3, II

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P5c FLAMMABLE LIQUIDS
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

(Contd. on page 9)



Page 9/9

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 23.08.2019 Version number 8 Revision: 06.11.2015

Trade name: UHU plus multifest (Härter)

(Contd. of page 8)

· Relevant phrases

H225 Highly flammable liquid and vapour.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H335 May cause respiratory irritation.

· Department issuing SDS: UHU QESH

· Contact: Dr. C. Hanf

· Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the

International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids - Category 2

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Skin Sens. 1: Skin sensitisation - Category 1

STOT SE 3: Specific target organ toxicity (single exposure) - Category 3

· * Data compared to the previous version altered.



Fax: 0049-(0)7223-284-245



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 23.08.2019 Version number 8 Revision: 30.03.2016

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: UHU plus multifest (Binder)
- 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- · Application of the substance / the mixture Adhesives
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

UHU GmbH & Co.KG Herrmannstraße 7 D-77815 Bühl (Baden) Tel.:0049-(0)7223-284-0

email: sds@uhu.boltongroup.de

• Further information obtainable from: UHU QESH • 1.4 Emergency telephone number:

Tel.: + 49 (0) 30/19240 (Notruf) Tel.: + 49 (0) 72 23/28 40

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Flam. Liq. 2 H225 Highly flammable liquid and vapour.



GHS05 corrosion

Skin Corr. 1A H314 Causes severe skin burns and eye damage.

Eye Dam. 1 H318 Causes serious eye damage.



Skin Sens. 1 H317 May cause an allergic skin reaction.

STOT SE 3 H335 May cause respiratory irritation.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

(Contd. on page 2)





Safety data sheet according to 1907/2006/EC, Article 31

Printing date 23.08.2019 Version number 8 Revision: 30.03.2016

Trade name: UHU plus multifest (Binder)

(Contd. of page 1)

· Hazard pictograms







GHS02 GHS05 GHS07

- · Signal word Danger
- · Hazard-determining components of labelling:

methyl methacrylate methacrylic acid

· Hazard statements

H225 Highly flammable liquid and vapour.

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.

H335 May cause respiratory irritation.

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children. P260 Do not breathe vapours. P280 Wear protective gloves.

P302+P352 IF ON SKIN: Wash with plenty of soap and water.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- PBT: Not applicable.vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.2 Mixtures
- · Description: Adhesive

· Dangerous components:		
CAS: 80-62-6	methyl methacrylate	50-100%
EINECS: 201-297-1	🚸 Flam. Liq. 2, H225; 🕦 Skin Irrit. 2, H315; Skin	
Reg.nr.: 01-2119452498-28-XXXX	Flam. Liq. 2, H225; Skin Irrit. 2, H315; Skin Sens. 1, H317; STOT SE 3, H335	
CAS: 79-41-4	methacrylic acid	10-25%
EINECS: 201-204-4	Skin Corr. 1A, H314; (1) Acute Tox. 4, H302;	
	Acute Tox. 4, H312	

· Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.

(Contd. on page 3)



Page 3/10

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 23.08.2019 Version number 8 Revision: 30.03.2016

Trade name: UHU plus multifest (Binder)

(Contd. of page 2)

· After inhalation:

Supply fresh air.

Seek medical treatment in case of complaints.

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

Supply fresh air; consult doctor in case of complaints.

After skin contact:

If skin irritation continues, consult a doctor.

Immediately wash with water and soap and rinse thoroughly.

- · After eye contact: Rinse opened eye for several minutes under running water.
- After swallowing:

Rinse out mouth and then drink plenty of water.

Drink plenty of water and provide fresh air. Call for a doctor immediately.

Do not induce vomiting; call for medical help immediately.

· 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

· 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- \cdot 5.2 Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

During heating or in case of fire poisonous gases are produced.

- · 5.3 Advice for firefighters
- · Protective equipment:

Wear self-contained respiratory protective device.

Do not inhale explosion gases or combustion gases.

No special measures required.

Mouth respiratory protective device.

· Additional information

Cool endangered receptacles with water spray.

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Particular danger of slipping on leaked/spilled product.

Mount respiratory protective device.

Ensure adequate ventilation

- 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Use neutralising agent.

Send for recovery or disposal in suitable receptacles.

(Contd. on page 4)



Page 4/10

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 23.08.2019 Version number 8 Revision: 30.03.2016

Trade name: UHU plus multifest (Binder)

(Contd. of page 3)

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Ensure good interior ventilation, especially at floor level. (Fumes are heavier than air).

Prevent formation of aerosols.

· Information about fire - and explosion protection:

Fumes can combine with air to form an explosive mixture.

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Keep respiratory protective device available.

· 7.2 Conditions for safe storage, including any incompatibilities

- · Storage:
- · Requirements to be met by storerooms and receptacles:

Store only in the original receptacle.

Provide solvent resistant, sealed floor.

Store in a cool location.

- · Information about storage in one common storage facility: Store away from oxidising agents.
- · Further information about storage conditions:

Store receptacle in a well ventilated area.

Keep container tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

- · Storage class: 3
- · 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- · Additional information about design of technical facilities: No further data; see item 7.
- · 8.1 Control parameters

· Ingredients with limit values that require monitoring at the workplace:			
80-62-6 methyl methacrylate			
IOELV (EU)	Short-term value: 100 ppm Long-term value: 50 ppm		
AGW (Germany)	Long-term value: 210 mg/m³, 50 ppm 2(I);DFG, EU, Y		
79-41-4 methacrylic acid			
AGW (Germany)	Long-term value: 180 mg/m³, 50 ppm 2 (I);DFG, Y		

· Additional information: The lists valid during the making were used as basis.

(Contd. on page 5)



Page 5/10

Safety data sheet according to 1907/2006/EC, Article 31

Version number 8 Revision: 30.03.2016 Printing date 23.08.2019

Trade name: UHU plus multifest (Binder)

(Contd. of page 4)

- · 8.2 Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Do not eat, drink, smoke or sniff while working.

The usual precautionary measures are to be adhered to when handling chemicals.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes and skin.

Avoid direct contact with the chemical/ the product/ the preparation by organisational measures.

· Respiratory protection:

Use suitable respiratory protective device when high concentrations are present.

Protection of hands:

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

After each cleaning use treatment creams, for very dry skin greasy ointments.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection: Goggles recommended during refilling

SECTION 9: Physical and chemical properties

- · 9.1 Information on basic physical and chemical properties
- · General Information
- · Appearance:

Form: Pastv Colour: Whitish **Pungent** · Odour: · Odour threshold:

Not determined.

· pH-value at 20 °C: 3.5

· Change in condition

Melting point/freezing point: Undetermined.

Initial boiling point and boiling range: 101 °C

· Flash point: 10 °C

· Flammability (solid, gas): Not applicable.

· Ignition temperature: 430 °C

(Contd. on page 6)



Page 6/10

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 23.08.2019 Version number 8 Revision: 30.03.2016

Trade name: UHU plus multifest (Binder)

	(Contd. of page
· Decomposition temperature:	Not determined.
· Auto-ignition temperature:	Product is not selfigniting.
· Explosive properties:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
· Explosion limits:	
Lower:	2.1 Vol %
Upper:	12.5 Vol %
· Vapour pressure at 20 °C:	47 hPa
· Density at 20 °C:	0.95076 g/cm ³
· Relative density	Not determined.
· Vapour density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with	
water:	Not miscible or difficult to mix.
· Partition coefficient: n-octanol/water:	Not determined.
· Viscosity:	
Dynamic at 20 °C:	48,000 mPas
Kinematic:	Not determined.
· Solvent content:	
VOC (EC)	0.00 %
Solids content:	30.0 %
· 9.2 Other information	All relevant physical data were determined for the mixture. All non determined data are not measurably
	not relevant for the characterization of the mixture.

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

· 10.3 Possibility of hazardous reactions

Forms explosive gases/fumes.

Reacts with strong oxidising agents.

Reacts with strong acids and alkali.

- 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: Flammable gases/vapours



Page 7/10

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 23.08.2019 Version number 8 Revision: 30.03.2016

Trade name: UHU plus multifest (Binder)

(Contd. of page 6)

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:				
80-62-6 methyl methacrylate				
Oral	LD50	7,872 mg/kg (rat)		
79-41-4 methacrylic acid				
Oral	LD50	1,332 mg/kg (mouse)		
Dermal	LD50	500 mg/kg (rabbit)		

- · Primary irritant effect:
- · Skin corrosion/irritation

Causes severe skin burns and eye damage.

· Serious eye damage/irritation

Causes serious eye damage.

· Respiratory or skin sensitisation

May cause an allergic skin reaction.

· Additional toxicological information:

Die Einstufung wurde aufgrund toxikologischer Untersuchungen vorgenommen.

- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- STOT-single exposure

May cause respiratory irritation.

- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water Must not reach sewage water or drainage ditch undiluted or unneutralised.

Do not allow product to reach ground water, water course or sewage system.

- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- 12.6 Other adverse effects No further relevant information available.



Page 8/10

according to 1907/2006/EC, Article 31

Printing date 23.08.2019 Version number 8 Revision: 30.03.2016

Trade name: UHU plus multifest (Binder)

(Contd. of page 7)

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Disposal must be made according to official regulations.

· European waste catalogue

08 04 09* waste adhesives and sealants containing organic solvents or other hazardous substances

- · Uncleaned packaging:
- · Recommendation:

Packagings that may not be cleansed are to be disposed of in the same manner as the product.

SECTION 14: Transport information	SECTION 14:	Transport	information
--	-------------	------------------	-------------

	14.	1 l	JN-	Nu	mber	•
--	-----	-----	-----	----	------	---

· ADR, IMDG, IATA UN1133

· 14.2 UN proper shipping name

· ADR 1133 ADHESIVES

1133 KLEBSTOFFE, Sondervorschrift 640H

· IMDG, IATA ADHESIVES

- · 14.3 Transport hazard class(es)
- · ADR, IMDG, IATA



· Class 3 Flammable liquids.

· Label 3

· 14.4 Packing group

· ADR, IMDG, IATA

· 14.5 Environmental hazards:

· Marine pollutant:

• 14.6 Special precautions for user Warning: Flammable liquids.

· Danger code (Kemler):

• **EMS Number:** F-E,S-D

· Stowage Category A

· 14.7 Transport in bulk according to Annex II

of Marpol and the IBC Code Not applicable.

(Contd. on page 9)



Page 9/10

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 23.08.2019 Version number 8 Revision: 30.03.2016

Trade name: UHU plus multifest (Binder)

(Contd. of page 8)

· Transport/Additional information:

· ADR

· Limited quantities (LQ) 5L

· Excepted quantities (EQ) Code: E1

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 1000

ml

• Transport category 3
• Tunnel restriction code E

· IMDG

· Limited quantities (LQ) 5L

· Excepted quantities (EQ) Code: E1

Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000

ml

· UN "Model Regulation": UN 1133 ADHESIVES, 3, III

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P5c FLAMMABLE LIQUIDS
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t
- REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H225 Highly flammable liquid and vapour.

H302 Harmful if swallowed.

H312 Harmful in contact with skin.

H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H335 May cause respiratory irritation.

· Department issuing SDS: UHU QESH

· Contact: Dr. C. Hanf

(Contd. on page 10)



Page 10/10

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 23.08.2019 Version number 8 Revision: 30.03.2016

Trade name: UHU plus multifest (Binder)

(Contd. of page 9)

Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Liq. 2: Flammable liquids – Category 2 Acute Tox. 4: Acute toxicity – Category 4

Skin Corr. 1A: Skin corrosion/irritation – Category 1A
Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation - Category 1

Skin Sens. 1: Skin sensitisation - Category 1

STOT SE 3: Specific target organ toxicity (single exposure) - Category 3

· * Data compared to the previous version altered.